NSN 4720-01-212-4783

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-212-4783

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
8.000 inches
Exterior Color:
Black
End Application:
Truck, fl (m10a)
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
2250.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber, synthetic err-100
Maximum Operating Pressure:
565.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:

Inside Surface Condition:

Oil resistant and weatherproof

Outer Covering Environmental Protection:

90.0 degrees 2nd end

Smooth

NSN 4720-01-212-4783

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
78.000 inches
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Un 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0