NSN 4720-01-215-3231

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-215-3231

Cross Sectional Snape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.390 inches
Minimum Inside Bending Radius:
1.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.000 inches
Thread Series Designator:
Unjf 1st end
Shelf Life:

NSN 4720-01-215-3231

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0