NSN 4720-01-215-3232

Nonmetallic Hose Assembly - Page 1 of 2



Cross Sectional Shape: Round Thread Class: 3b 1st end Thread Discritoris: Right-hand 1st end Inside Diameter: 0.212 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Cutside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end End Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 18000.0 pounds per square inch Layer Composition And Location: Unter layer braided corrosion resistant steel wire Maximum Operating Pressure: 6000.0 pounds per square inch	View Online at https://aerobasegroup.com/nsn/4720-01-215-3232
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.212 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Sträight 1st end Connection Type: Threaded internal tube 1st end Endeatures Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Cross Sectional Shape:
3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.212 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Round
Thread Direction: Right-hand 1st end Inside Diameter: 0.212 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Thread Class:
Right-hand 1st end Inside Diameter: 0.212 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	3b 1st end
Inside Diameter: 0.212 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Thread Direction:
Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Right-hand 1st end
Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Inside Diameter:
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	0.212 inches
Outside Diameter: 0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Tempurature Rating:
0.390 inches Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Minimum Inside Bending Radius: 1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Outside Diameter:
1.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	0.390 inches
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Minimum Inside Bending Radius:
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	1.500 inches
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Connection Style:
Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Swivel nut flare 1st end
Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	End Connection Design:
Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Straight 1st end
Features Provided: Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Connection Type:
Electrostatic discharge capability Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Threaded internal tube 1st end
Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Features Provided:
16000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Electrostatic discharge capability
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	Burst Test Pressure:
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:	16000.0 pounds per square inch
Maximum Operating Pressure:	Layer Composition And Location:
	Outer layer braided corrosion resistant steel wire
3000.0 pounds per square inch	Maximum Operating Pressure:
	3000.0 pounds per square inch
Thread Size:	Thread Size:
0.438 inches 1st end	0.438 inches 1st end
Seat Angle:	Seat Angle:
37.0 degrees 1st end	37.0 degrees 1st end
Hydrostatic Test Pressure:	Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and solvent resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.375 inches

Thread Series Designator:

Unjf 1st end

NSN 4720-01-215-3232

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0