

View Online at <https://aerobasegroup.com/nsn/4720-01-215-4293>

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Tempurature Rating:**

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit

**Outside Diameter:**

1.203 inches

**Minimum Inside Bending Radius:**

7.375 inches

**First End Connection Type:**

Threaded internal tube

**First End Thread Class:**

2b

**First End Thread Direction:**

Right-hand

**First End Seat Angle In Deg:**

37.0

**First End Connection Design:**

Straight

**Hose Or Tubing Specification/std Data:**

Mil-h-13444, type 3 specification

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting zinc 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

1500.0 pounds per square inch

**First End Swivel Action Capability:**

Included

**Maximum Operating Pressure:**

375.0 pounds per square inch

**First End Thread Qty Per Inch (tpi):**

12

**First End Thread Series Designator:**

Un

**Seat Angle:**

37.0 degrees 1st end

**First End Thread Size:**

1.312 inches

**Hydrostatic Test Pressure:**

750.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and ozone resistant and oil resistant and mildew resistant and vibration resistant

**Vacuum In Torr:**

381.0

**Inside Surface Condition:**

Smooth

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-13444 spec.