

View Online at <https://aerobasegroup.com/nsn/4720-01-216-4077>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.312 inches

Minimum Inside Bending Radius:

2.000 inches

Hose Or Tubing Specification/std Data:

Mil-h-25579 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nuts drilled for lockwire

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.000 inches working

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 26512, 50599 and 78570 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Unf 1st end

Specification Data:

Mil-h-25579 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.