

View Online at <https://aerobasegroup.com/nsn/4720-01-216-6755>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.516 inches

Minimum Inside Bending Radius:

0.750 inches

Exterior Color:

Blue

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 2nd end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

20 2nd end

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyester cord and 2nd layer braided wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

28.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

50.000 inches

Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

Thread Series Designator:

Uns 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0