Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-217-4770

Cros	s Sectional Shape:
Roun	ld
Threa	ad Class:
3b 1s	st end
Threa	ad Direction:
Right	-hand 1st end
Insid	e Diameter:
0.212	2 inches
Temp	ourature Rating:
-67.0	degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outs	ide Diameter:
0.415	5 inches
Minir	num Inside Bending Radius:
1.500) inches
Conr	nection Style:
Swive	el nut flare 2nd end
End	Connection Design:
Straig	ght 1st end
Conr	nection Type:
Threa	aded internal tube 1st end
Burs	t Test Pressure:
1200	0.0 pounds per square inch
Laye	r Composition And Location:
Outer	r layer braided corrosion resistant steel wire
Maxi	mum Operating Pressure:
3000	.0 pounds per square inch
Threa	ad Size:
0.438	3 inches 1st end
Seat	Angle:
37.0	degrees 2nd end
Hydr	ostatic Test Pressure:
6000	.0 pounds per square inch
Flow	Angle:
90.0	degrees 2nd end
Insid	e Surface Condition:
Smoo	oth
Meas	suring Method And Length:
5.500) inches working
Threa	ad Series Designator:
Unjf 1	1st end
Shelf	f Life:
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0