

View Online at <https://aerobasegroup.com/nsn/4720-01-218-4638>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.344 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.547 inches

**Minimum Inside Bending Radius:**

2.500 inches

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

0.562 inches 2nd end

**Seat Angle:**

45.0 degrees 2nd end

**Hydrostatic Test Pressure:**

2500.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Fire resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

85.500 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 2nd end

**Specification Or Standard:**

6 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0