Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-218-8391

# **Cross Sectional Shape:**

Round

**Thread Class:** 

2b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.375 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

### **Outside Diameter:**

0.844 inches

Minimum Inside Bending Radius:

#### 5.000 inches

**Exterior Color:** 

# Black

End Application:

Mx missile

#### **Connection Style:**

Swivel nut flare 1st end

## End Connection Design:

Straight 1st end

# Connection Type:

Threaded internal tube 1st end

# Features Provided:

Reusable end fittings

### **Burst Test Pressure:**

16000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic

### Maximum Operating Pressure:

4000.0 pounds per square inch

**Thread Size:** 

0.562 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

### Hydrostatic Test Pressure:

8000.0 pounds per square inch

# Criticality Code Justification:

Feat

# Inside Surface Condition:

Smooth



Measuring Method And Length: 900.000 inches **Special Features:** Weapon system essential Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0