

View Online at <https://aerobasegroup.com/nsn/4720-01-218-8998>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 180.0 degrees fahrenheit single response

Outside Diameter:

0.810 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Swivel, plain 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 1st end

Burst Test Pressure:

40000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally wrapped corrosion resistant steel fabric and 2nd layer spirally wrapped corrosion resistant steel fabric and 3rd layer spirally wrapped corrosion resistant steel fabric and 4th layer spirally wrapped corrosion resistant steel fabric and 5th layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

10000.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

120.000 inches

Media For Which Designed:

Water single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0