NSN 4720-01-219-1396

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-219-1396

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 180.0 degrees fahrenheit single response
Exterior Color:
Black
End Application:
Fire truck, 71l22, a/s32p8
Connection Style:
Plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
24 1st end
Burst Test Pressure:
4500.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided fabric and 2nd layer rubber impregnated braided fabric and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Corrosion resistant and ozone resistant and mildew resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.000 inches
Special Features:
Second end has female bulkhead 0.625-18 with jam nut

Media For Which Designed:

Brake fluid, nonmineral oil single response

NSN 4720-01-219-1396

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hread	Series	Designator:	

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0