## NSN 4720-01-219-2029

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-219-2029

| Cross Sectional Shape:   |
|--|
| Round  |
| Inside Diameter:   |
| 1.380 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response                                      |
| Bolt Circle Diameter:  |
| 3.120 inches 2nd end   |
| Flange Thickness:  |
| 0.440 inches 2nd end   |
| Outside Diameter:  |
| 1.750 inches   |
| Minimum Inside Bending Radius:   |
| 10.500 inches  |
| Bolt Hole Quantity:  |
| 4 2nd end  |
| Flange Outside Diameter:   |
| 4.250 inches 2nd end   |
| Connection Style:  |
| Raised 2nd end   |
| Bolt Hole Diameter:  |
| 0.560 inches 2nd end   |
| Raised Face Diameter:  |
| 2.120 inches 2nd end   |
| End Flange Construction:   |
| Solid 2nd end  |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Raised face flange 2nd end   |
| Features Provided:   |
| Reusable end fittings  |
| Burst Test Pressure:   |
| 1600.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:  |
| 400.0 pounds per square inch   |
| Hydrostatic Test Pressure:   |
| 800.0 pounds per square inch   |
| Flow Angle:  |
| 90.0 degrees 2nd end   |

## NSN 4720-01-219-2029

Nonmetallic Hose Assembly - Page 2 of 2



| Inside Surface Condition:             |
|---------------------------------------|
| Smooth                                |
| Measuring Method And Length:          |
| 14.000 inches working                 |
| Flange Style:                         |
| Round w/ bolt holes 2nd end           |
| Media For Which Designed:             |
| Fuel/oil, hydrocarbon single response |
| Shelf Life:                           |
| N/a                                   |
| Unit Of Measure:                      |
|                                       |
| Demilitarization:                     |
| No                                    |

**Fiig:** A542a0