NSN 4720-01-219-4289



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-219-4289 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** Between 0.875 inches and 0.938 inches **Minimum Inside Bending Radius:** 7.000 inches **Connection Style:** Swivel, plain 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Outer Covering Environmental Protection:** Oil resistant and weatherproof **Inside Surface Condition:**

Smooth

Measuring Method And Length:

20.000 inches

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

NSN 4720-01-219-4289

Nonmetallic Hose Assembly - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A542a0