

View Online at <https://aerobasegroup.com/nsn/4720-01-220-0913>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-3992, type 1, class 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Quick Disconnect Size:**

0.375 inches 2nd end

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting steel 2nd end

**Connection Type:**

Threaded external pipe 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

900.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, synthetic err-100

**Thread Size:**

0.500 inches 1st end

**External Protection Type And Location (non-core):**

Both ends spring guard, round steel coil

**Outer Covering Environmental Protection:**

Age resistant and mildew resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

70.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

External protection type and location- both ends spring guard, round steel coil , inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Nptf 1st end

**Specification Data:**

96906-ms39325 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-3992 spec.