## NSN 4720-01-220-0915

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-220-0915	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.212 inches	
Tempurature Rating:	
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Outside Diameter:	
0.390 inches	
Minimum Inside Bending Radius:	
1.500 inches	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 2nd end	

### **Hydrostatic Test Pressure:**

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

#### **Outer Covering Environmental Protection:**

Fuel resistant and heat resistant and oil resistant and solvent resistant

#### **Inside Surface Condition:**

Smooth

#### **Measuring Method And Length:**

37.375 inches working

# NSN 4720-01-220-0915

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0