

View Online at <https://aerobasegroup.com/nsn/4720-01-220-0916>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.391 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.905 inches

**Minimum Inside Bending Radius:**

2.875 inches

**End Application:**

Aircraft, harrier av-8b

**Connection Style:**

Swivel nut, inverted flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

20 2nd end

**Burst Test Pressure:**

14000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.719 inches 2nd end

**Seat Angle:**

8.5 degrees 2nd end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

20.0 degrees 2nd end

**Criticality Code Justification:**

Feat

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

23.500 inches working

**Special Features:**

Weapon system essential

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources; 00624 and 76301 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos after 1984

**Thread Series Designator:**

Unjs 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0