Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-220-2029

| view Online at https://aeiobasegioup.com/hsi//4/20-01-220-2029 |
|---|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.124 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.344 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 2000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 300.0 pounds per square inch |
| Thread Size: |
| 0.312 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Weatherproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 5.850 inches |
| Media For Which Designed: |
| Water single response |

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0