NSN 4720-01-220-2034

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-220-2034
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.298 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.475 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and solvent resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.875 inches working

Thread Series Designator:

Unjf 1st end

NSN 4720-01-220-2034

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0