## NSN 4720-01-220-6653

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-220-6653

| Cross Sectional Shape:   |
|--|
| Round  |
| Inside Diameter:   |
| 1.810 inches   |
| Outside Diameter:  |
| 2.220 inches   |
| Minimum Inside Bending Radius:   |
| 13.250 inches  |
| Features Provided:   |
| Reusable end fittings  |
| Burst Test Pressure:   |
| 1400.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:  |
| 350.0 pounds per square inch   |
| Hydrostatic Test Pressure:   |
| 700.0 pounds per square inch   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 17.000 inches  |
| Extra Long Reference Number:   |
| 2580-32-190016-1.25-190016-1.25-17   |
| Reference Number Differentiating Characteristics:  |
| As differentiated by pac elrn  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A542a0   |
|  |
|  |