## NSN 4720-01-222-6015



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-222-6015 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.250 inches **Minimum Inside Bending Radius:** 9.500 inches **Exterior Color:** Blue Angle Between Rigid Elbow Fittings In Deg: 170.0 **End Application:** 2320-01-123-1608 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 12500.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and 2nd layer braided wire and 3rd layer molded rubber, synthetic **Maximum Operating Pressure:** 3125.0 pounds per square inch **Thread Size:** 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees 1st end

Smooth

**Measuring Method And Length:** 

**Inside Surface Condition:** 

65.000 inches

## NSN 4720-01-222-6015

Nonmetallic Hose Assembly - Page 2 of 2



| Me | dia | For | Which | Design | ed: |
|----|-----|-----|-------|--------|-----|
|    |     |     |       |        |     |

Fuel/oil, hydrocarbon and hydraulic fluid, water base single response

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0