NSN 4720-01-222-6020



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-222-6020 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.790 inches **Minimum Inside Bending Radius:** 5.000 inches **Exterior Color:** Blue **End Application:** 2320-01-123-1608 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer molded rubber, ethylene propylene **Maximum Operating Pressure:** 3500.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 7000.0 pounds per square inch **Inside Surface Condition:**

Smooth

Measuring Method And Length:

43.500 inches

Thread Series Designator:

Unf 1st end

NSN 4720-01-222-6020

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0