## NSN 4720-01-222-6031

Un 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-222-6031

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.750 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response                               |
| Outside Diameter:   |
| 1.250 inches  |
| Minimum Inside Bending Radius:  |
| 9.500 inches  |
| Exterior Color:   |
| Blue  |
| End Application:  |
| 2320-01-123-1608  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 2nd end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Thready Qty Per Inch (tpi):   |
| 12 2nd end  |
| Burst Test Pressure:  |
| 9000.0 pounds per square inch   |
| Layer Composition And Location:   |
| 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, ethylene propylene |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 1.062 inches 2nd end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 26.500 inches   |
| Thread Series Designator:   |

## NSN 4720-01-222-6031

Nonmetallic Hose Assembly - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0