NSN 4720-01-223-2511

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-223-2511

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-20.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.390 inches
Minimum Inside Bending Radius:
1.750 inches
Exterior Color:
Black
Angle Between Rigid Elbow Fittings In Deg:
0.0
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Perforated outer cover
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer braided polyamide cord and outer layer molded plastic
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Outer Covering Environmental Protection.

Abrasion resistant and oil resistant and waterproof

NSN 4720-01-223-2511

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length
15.750 inches working
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0