NSN 4720-01-223-7778

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-223-7778

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-20.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.391 inches
Minimum Inside Bending Radius:
1.750 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Perforated outer cover
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer braided polyamide cord and outer layer braided polyamide cord
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.250 inches working
Thread Series Designator:

Unjf 1st end

NSN 4720-01-223-7778

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0