Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-223-7781

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees celsius and 85.0 degrees celsius single response
Outside Diameter:
0.480 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1250.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Vacuum In Torr:
20.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
6.000 inches
Special Features:
Yellow chafe guard

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0