

View Online at <https://aerobasegroup.com/nsn/4720-01-223-7782>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees celsius and 85.0 degrees celsius single response

Outside Diameter:

0.480 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

1250.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Vacuum In Torr:

20.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

8.500 inches

Special Features:

Red chafe guard

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0