NSN 4720-01-223-8679

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-223-8679

Right-hand 1st end
Inside Diameter:
0.310 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.460 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
7500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Ester resistant and fuel resistant and oil resistant and solvent resistant and vibration resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.350 inches

NSN 4720-01-223-8679

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Second end has two 90 degree elbows spaced 1.921 in. Center to center

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0