NSN 4720-01-224-3058

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-224-3058

| Cross Costional Change |
|---|
| Cross Sectional Shape: |
| Round |
| Inside Diameter: |
| 1.000 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.500 inches |
| Minimum Inside Bending Radius: |
| 12.000 inches |
| Exterior Color: |
| Black |
| Angle Between Rigid Elbow Fittings In Deg: |
| 278.0 |
| Flange Outside Diameter: |
| 1.750 inches 1st end |
| Connection Style: |
| Plain 1st end |
| End Flange Construction: |
| Solid 1st end |
| End Connection Design: |
| Elbow 1st end |
| Connection Type: |
| Plain face flange 1st end |
| Burst Test Pressure: |
| 8000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 2000.0 pounds per square inch |
| Hydrostatic Test Pressure: |
| 4000.0 pounds per square inch |
| Flow Angle: |
| 45.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Abrasion resistant and oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 28.000 inches |
| Flange Style: |
| Round w/ out bolt holes 1st end |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response and grease single response and gas single response and water single response and air single |
| response |

NSN 4720-01-224-3058

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0