## NSN 4720-01-224-5411

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-224-5411

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.656 inches
Minimum Inside Bending Radius:
5.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Vacuum In Torr:
0.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
96.000 inches
Thread Series Designator:
Unjf 1st end

## NSN 4720-01-224-5411

Nonmetallic Hose Assembly - Page 2 of 2



Specificatio	n Data:
--------------	---------

96906-ms8000 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0