

View Online at <https://aerobasegroup.com/nsn/4720-01-225-1406>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.625 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 265.0 degrees fahrenheit single response

Outside Diameter:

0.828 inches

Minimum Inside Bending Radius:

2.875 inches

Exterior Color:

Natural

End Application:

B-1b aircraft

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

120.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

240.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and corrosion resistant

Inside Surface Condition:

Convoluted

Measuring Method And Length:

12.060 inches working

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 00624 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0