Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-225-2780

Cross Secti	onal Shape:
Round	
Thread Clas	;S:
3b 1st end	
Thread Dire	ction:
Right-hand 1	st end
Inside Diam	eter:
0.406 inches	i
Tempuratur	e Rating:
-65.0 degree	es fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Dia	meter:
0.585 inches	
Minimum In	side Bending Radius:
4.620 inches	
Connection	Style:
Swivel nut fla	are 1st end
End Connec	ction Design:
Straight 1st	end
Connection	Туре:
Threaded inf	ternal tube 1st end
Burst Test I	Pressure:
6000.0 poun	ds per square inch
Layer Comp	position And Location:
Outer layer b	praided corrosion resistant steel wire
Maximum C	perating Pressure:
1500.0 poun	ds per square inch
Thread Size	:
0.750 inches	s 1st end
Seat Angle:	
37.0 degrees	s 1st end
Hydrostatic	Test Pressure:
3000.0 poun	ds per square inch
Inside Surfa	ace Condition:
Smooth	
Measuring I	Method And Length:
8.000 inches	;
Thread Seri	es Designator:
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Mea	sure:

NSN 4720-01-225-2780

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

