Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-228-1596

Cross Sectional Sh	ape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.298 inches	
Tempurature Ratin	g:
67.0 degrees fahre	heit and 400.0 degrees fahrenheit single response
Dutside Diameter:	
).475 inches	
Minimum Inside Be	nding Radius:
2.500 inches	
Connection Style:	
Swivel nut, flareless	2nd end
End Connection De	sign:
Straight 1st end	
Connection Type:	
Threaded internal tu	be 1st end
eatures Provided	
lectrostatic dischar	ge capability and reusable end fittings
Burst Test Pressur	e:
000.0 pounds per s	quare inch
ayer Composition	And Location:
Duter layer braided	corrosion resistant steel wire
Maximum Operatin	g Pressure:
500.0 pounds per s	quare inch
hread Size:	
).562 inches 2nd er	d
Seat Angle:	
12.0 degrees 2nd er	d
Hydrostatic Test P	ressure:
3000.0 pounds per s	quare inch
Flow Angle:	
45.0 degrees 2nd er	d
Duter Covering En	vironmental Protection:
Ethylene glycol resis	tant and fuel resistant and heat resistant and hydraulic solution resistant and oil resistant and solvent resistant and
vibration resistant	
Inside Surface Cor	dition:
Smooth	
	And Length:

33.000 inches working

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0