## NSN 4720-01-228-5243

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-228-5243

| Cross Sectional Shape:  |
|---|
| Round   |
| Inside Diameter:  |
| 0.190 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response                                 |
| Outside Diameter:   |
| 0.520 inches  |
| Minimum Inside Bending Radius:  |
| 3.000 inches  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal hose 1st end  |
| Burst Test Pressure:  |
| 12000.0 pounds per square inch  |
| Layer Composition And Location:   |
| 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Outer Covering Environmental Protection:  |
| Cold resistant and mildew resistant and oil resistant   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 72.000 inches excluding end fittings  |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A542a0  |
|   |
|   |