NSN 4720-01-229-3021

37.0 degrees 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-229-3021

Cross Sectional Snape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-55.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.672 inches
Minimum Inside Bending Radius:
1.250 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting cadmium 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Second End Relationship With First End:
Identical
Burst Test Pressure:
6000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided polyester cord err-100
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:

NSN 4720-01-229-3021

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
3000.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.000 inches
Special Features:
ld strap p/n ms3368-1-9b furnished
Media For Which Designed:
Air single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ5/220