Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-229-3022

С	ross Sectional Shape:
	bund
	nread Class:
) 1st end
	nread Direction:
	ight-hand 1st end
	side Diameter:
	406 inches
-	empurature Rating:
	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	utside Diameter:
	562 inches
-	inimum Inside Bending Radius:
	462 inches
-	onnection Style:
	wivel nut flare 2nd end
-	nd Connection Design:
	raight 1st end
	onnection Type:
	nreaded internal tube 1st end
Fe	eatures Provided:
Re	eusable end fittings
В	urst Test Pressure:
80	000.0 pounds per square inch
La	ayer Composition And Location:
O	uter layer braided corrosion resistant steel wire
M	aximum Operating Pressure:
15	500.0 pounds per square inch
Tł	nread Size:
0.	750 inches 2nd end
Se	eat Angle:
37	7.0 degrees 2nd end
Hy	ydrostatic Test Pressure:
30	000.0 pounds per square inch
FI	ow Angle:
90	0.0 degrees 2nd end
In	side Surface Condition:
Sr	nooth
M	easuring Method And Length:
16	6.000 inches working
Tł	nread Series Designator:
l Ir	nf 2nd end

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Specification Data:

96906-ms8000 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0