NSN 4720-01-229-3026

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-229-3026

| -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response |
|----------------------------------------------------------------------------------------------|
| Outside Diameter: |
| 0.500 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 1250.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided cotton cord and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 400.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Abrasion resistant and weatherproof and fuel resistant and oil resistant and water resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 11.875 inches working |
| |
| |
| |

NSN 4720-01-229-3026

Nonmetallic Hose Assembly - Page 2 of 2



| Media For Which Designed: |
|----------------------------------|
| Air single response |
| Thread Series Designator: |
| Unf 1st end |
| Specification Data: |
| 88044-an6270 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A542a0