Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-229-3974

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.060 inches
Minimum Inside Bending Radius:
5.000 inches
Quick Disconnect Size:
0.750 inches 2nd end
Connection Style:
Push (internal) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
1200.0 pounds per square inch
Layer Composition And Location:
1st layer braided rayon cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
99.000 inches
Thread Series Designator:
Nptf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4720-01-229-3974

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

