

View Online at <https://aerobasegroup.com/nsn/4720-01-229-7300>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.625 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.932 inches

Minimum Inside Bending Radius:

6.000 inches

End Application:

J.I. Case backhoe loader, models 680e and 680g

Connection Style:

Flared 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

11000.0 pounds per square inch

Layer Composition And Location:

1st layer braided wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

2750.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

58.000 inches

Special Features:

Aeroquip part no. Fe101a shielding clamp is connected to the male fitting

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0