NSN 4720-01-229-7303



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-229-7303 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.910 inches **Minimum Inside Bending Radius:** 6.000 inches **End Application:** Electrical fork lift pettibone corporation model no 1a4011exs **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end Vacuum In Torr: 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 47.740 inches **Thread Series Designator:**

Unf 1st end

Shelf Life:

Onen Ene

N/a

NSN 4720-01-229-7303

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0