NSN 4720-01-229-7304

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-229-7304

Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1250.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and weatherproof and fuel resistant and oil resistant and water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.125 inches working

NSN 4720-01-229-7304

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Air single response
Thread Series Designator:
Unf 1st end
Specification Data:
88044-an6270 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0