NSN 4720-01-230-3646

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-230-3646

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.860 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Connection Style:
External seat for gasket seal (boss) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external boss 2nd end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3500.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.500 inches
Media For Which Designed:

NSN 4720-01-230-3646

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Carias	Decimates
illieau	oenes	Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0