Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-230-9327

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.735 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
Between 0.910 inches and 0.950 inches
Minimum Inside Bending Radius:
9.000 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
500.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber or 1st layer spirally wrapped fabric and 2nd layer rubber impregnated braided fabric
Maximum Operating Pressure:
125.0 pounds per square inch
Thread Size:
1.0625 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
250.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
47.875 inches excluding end fittings and 48.625 inches excluding end fittings
Thread Series Designator:
Unj 1st end
Shelf Life:

N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0