

View Online at <https://aerobasegroup.com/nsn/4720-01-231-5333>

Cross Sectional Shape:

Round

Inside Diameter:

2.000 inches

Tempurature Rating:

-32.0 degrees fahrenheit single response

Outside Diameter:

2.500 inches

Hose Or Tubing Specification/std Data:

Mil-prf-11588, type 3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil-c-27487, type 6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Second End Fitting Specification/std Data:

Mil-c-27487, type 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Quick Disconnect Size:

2.000 inches 2nd end

End Application:

3835-01-182-1977

Connection Style:

Cam or lever (internal) 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting aluminum alloy all ends

Connection Type:

Internal quick disconnect 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

400.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer rubber impregnated cotton fabric err-100 or 1st layer rubber impregnated fabric err-100

Unable To Decode:

Unable to decode or unable to decode

Maximum Operating Pressure:

100.0 pounds per square inch

Unable To Decode:

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.0 feet

Second End Swivel Action Capability:

Not included

Specification Data:

81349-mil-prf-11588 government specification

Specification Or Standard:

1 class and 3 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-11588 spec.