NSN 4720-01-231-6676

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-231-6676 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.410 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.770 inches **Minimum Inside Bending Radius:** 4.625 inches **Exterior Color:** Black **Connection Style:** Swivel, plain 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.500 inches 1st end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Outer Covering Environmental Protection:** Mildew resistant and oil resistant **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:**

120.000 inches

Thread Series Designator:

Nptf 1st end

NSN 4720-01-231-6676

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0