# NSN 4720-01-232-2862

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-232-2862 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees celsius and 85.0 degrees celsius single response **Outside Diameter:** 0.480 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 1250.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle:

37.0 degrees 1st end

## **Hydrostatic Test Pressure:**

400.0 pounds per square inch

## **Outer Covering Environmental Protection:**

Alcohol resistant and fuel resistant and oil resistant and water resistant

**Inside Surface Condition:** 

Smooth

# **Measuring Method And Length:**

10.500 inches

#### **Special Features:**

White chafe guard

# NSN 4720-01-232-2862

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docionatori
ı	meau	oenes	Designator:

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0