NSN 4720-01-234-4814

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-234-4814

Cross Sectional Snape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.812 inches
Minimum Inside Bending Radius:
7.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.750 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end

NSN 4720-01-234-4814

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0