## NSN 4720-01-235-3095

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-235-3095

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.516 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
85.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Unf 2nd end

## NSN 4720-01-235-3095

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0