

View Online at <https://aerobasegroup.com/nsn/4720-01-235-3336>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

**Outside Diameter:**

0.469 inches

**Minimum Inside Bending Radius:**

4.000 inches

**End Application:**

1510-00-715-9379

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

1200.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided fiber and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

400.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

11.625 inches working

**Thread Series Designator:**

Unf 1st end

**Specification Data:**

88044-an6270 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0