Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-235-3556

	ional Shape:
Round	
Thread Cla	SS:
2b 1st end	
Thread Dire	
Right-hand	
Inside Dian	
1.500 inche	
Tempuratu	-
-	es fahrenheit and 250.0 degrees fahrenheit single response
Outside Dia	
2.130 inche	-
	nside Bending Radius:
20.000 inch	
Connectior	
Swivel nut fl	
	ection Design:
Straight 1st	
Connectior	п Туре:
Threaded in	nternal tube 1st end
Features P	rovided:
Reusable er	nd fittings
Thready Qt	ty Per Inch (tpi):
12 1st end	
Burst Test	Pressure:
5000.0 pour	nds per square inch
Layer Com	position And Location:
1st layer bra	aided wire and 2nd layer braided wire and outer layer wrapped rubber, chloroprene
Maximum C	Operating Pressure:
1250.0 pour	nds per square inch
Thread Size	e:
1.875 inche	s 1st end
Seat Angle	:
37.0 degree	es 1st end
Hydrostatio	c Test Pressure:
2500.0 pour	nds per square inch
Inside Surf	ace Condition:
Smooth	
Measuring	Method And Length:
30.000 inch	es
Media For V	Which Designed:
Fuel/oil by	drocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0