NSN 4720-01-235-9629

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-235-9629

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.484 inches
Minimum Inside Bending Radius:
1.000 inches
End Application:
Truck chassis 5 ton m941
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.810 inches and 26.190 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Unf 1st end

Thread Series Designator:

NSN 4720-01-235-9629

Nonmetallic Hose Assembly - Page 2 of 2



_				
•	hο	·It	ife	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0